

ProRad Angles

ProRad Corner Protection Angles and Trims provide protection to vulnerable corners and are available in a variety of sizes. Any situation where corners are subject to vehicular or pedestrian traffic or any other form of abuse, ProRad Angles are the ideal solution.

Manufactured from Vinylac, it is quick and easy to install and has a stippled finish to help conceal the effects of impact and abrasion. ProRad Angles are supplied in a wide variety of colours and are the perfect compliment to the other types of rail in our ProRad range. It is available in lengths of 3.5m and 1.15m to suit and gives double impact deflection.

Standard and optional features;

Design:

- Simple and fast installation with adhesive tape
- Dimensions: **Standard is 75mm x 75mm x 90°** in lengths of 3.500m and 1.150m. A range of corner trims/angles are also available in 3.500mm lengths in various sizes, as illustrated
- Other widths of 25mm, 38mm, 50mm, 65mm are available
- Lengths of 3.5m and 1.15m
- Standard colours are black, light grey & dark grey - other colours are available on request
- Vinylac Angles and Trims with a smooth surface are available in a limited colour range
- Special colours and finishes available subject to order quantity

Installation

- When fixing ProRad Standard Angle or Corner Trim/Angle, ensure that both surfaces are completely clean, dry and flat
- Apply double sided adhesive tape lineally to each* internal face at approx. 3mm from each outside edge of the ProRad angle, peel off backing paper and place corner angle in position, applying uniform pressure. Should it not be practical to fix the corner angle with tape, fixing can be carried out by using screws and plugs as detailed
- *When fixing 25 x 25mm and 38 x 38mm Corner Trims the double sided adhesive tape should be fixed to one internal face only. All lengths come complete with double sided adhesive tape for fixing to pre-prepared wall surfaces



Order Information

Can be supply only or fully installed

